



EN 13967

09

1213

DECLARATION OF PERFORMANCE

No. 02313967020702**1. Product Type:**

Unique identification code of the product-type:

NOVOPROOF® DA-K**2. Type**

batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

DA-K Effective thickness 1.3 mm (lot no. see packaging)**3. Intended use**

or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Elastomeric waterproofing sheet made of Ethylen-Propylen-Dien-Terpolymer (EPDM) with fleece-backing $\leq 80 \text{ g/m}^2$ according to EN 13967 damp proof sheets (Type A)**basement tanking sheets (Type T)****4. Name, registered trade name**

or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**NOVOPROOF®
DURAPROOF technologies GmbH
Eisenbahnstr. 24
D - 66687 Wadern-Büschfeld
GERMANY****5. Contact Address:**

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)**6. AVCP:**

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+**7. Notified body:**

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**1213
Notified factory production control certification body No. 1213 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, 1213-CPR-023**

8. Notified body:

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant (see 7)

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Visible defects	passed	EN 1850-2	EN 13967:2012
Length	- 0 % / + 5 %	EN 1848-2	
Width	- 0.5 % / + 1.0 %	EN 1848-2	
Straightness	≤ 50 mm	EN 1848-2	
Flatness	≤ 10 mm	EN 1848-2	
Mass per unit area	1600 g/m ² [- 5 % / + 10 %]	EN 1849-2	
Effective Thickness	1.3 mm [- 5 % / + 10 %]	EN 1849-2	
Water tightness	passed	EN 1928 B	
Reaction to fire	Klasse E	EN ISO 11925-2 EN 13501-1	
Joint shear resistance	≥ 250 N/50 mm	EN 12317-2	
Tensile strength	≥ 6 N/mm ²	EN 12311-2	
Elongation	≥ 400 %	EN 12311-2	
Resistance to impact	≥ 2000 mm	EN 12691 B	
Resistance to static loading	> 20 kg	EN 12730 B	
Tear resistance	≥ 100 N	EN 12310-1	
Effects of liquid chemicals, including water (23 °C/28 d)	passed	EN 1847	
Water vapour properties	60000 ± 18000	EN 1931	
Durability of watertightness against ageing	passed	EN 1296 EN 1928	
Exposure to bitumen	passed	EN 1548	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Wadern-Büschfeld, 01. May 2014

Udo Bächler
General Manager

Ecology, Health and Safety Information

A Safety Data Sheet following EC-Regulation 1907/2006, Article 31 is not needed to bring the product to the market, to transport or to use it. The product does not damage the environment when used as specified.

REACH

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).
