

## Declaration of Performance

No. 0001385909130

### 1. Product Type

Unique identification code of the product-type:

**NovoProof®**

### 2. Type

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**FAI, thickness 1,3 mm**

### 3. Intended use

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Elastomeric membrane as underlay for walls  
made of butyl rubber (IIR)  
according to EN 13859-2  
without lamination**

### 4. Name, registered trade name

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**NovoProof®  
CQLT SaarGummi Deutschland GmbH  
Eisenbahnstraße 24  
D-66687 Wadern-Büschfeld  
GERMANY**

### 5. System for the evaluation of performance stability

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 3**

### 6. Notified body

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**MPA BS 022  
The notified body No 022 has carried out the  
initial verification of the products**

## 7. Declared performance

| Essential characteristics        | Performance          | Test standard   | Harmonised technical specification |
|----------------------------------|----------------------|---|------------------------------------|
| Reaction to fire                 | Class E              | EN 13501-1<br>EN ISO 11925-2  | EN 13859-2:2010                    |
| Resistance to water permeability | W1                   | EN 1928 A   |                                    |
| Water vapour permeability $\mu$  | 156.000 $\pm$ 46.000 | EN 1931   |                                    |
| Tensile strength                 | $\geq$ 300 N/50mm    | EN 12311-1 A  |                                    |
| Elongation                       | $\geq$ 250 %         | EN 12311-1 A  |                                    |
| Tear resistance                  | $\geq$ 95 N          | EN 12310-1  |                                    |
| Cold bending (flexibility)       | $\leq$ -30°C         | EN 1109   |                                    |
| Artificial ageing regarding:     |                      |   |                                    |
| Resistance to water permeation   | W1                   | Artificial ageing under combined continuous exposure to UV radiation and increased temperature according to Annex C |                                    |
| Tensile strength                 | $\geq$ 270 N/50mm    |   |                                    |
| Elongation                       | $\geq$ 200 %         |   |                                    |

The performance of the above product is in conformity with the declared performance. The manufacturer referred to above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:  
Wadern-Büschfeld, 04.02.2022



**Piotr Gaska**  
Managing Director